



Hi-ULTRA

Single Zone Ductless Heat Pump

09K-12K-18K-24K BTU

R410A



*: follow instruction on service manual
or from your distributors



Hisense Canada

Specifications



BTU	9,000	12,000	18,000	24,000
Capacity (Cooling / Heating) (Btu/h)	9,000 / 10,000	12,000 / 12,000	18,000 / 19,000	24,000 / 26,000
Capacity (Heating at -5°F) (Btu/h)	8,500	9,500	15,000	19,500
SEER2 / HSPF2	25 / 10.5	23.5 / 9.5	20.5 / 9.5	21 / 10
Sound Pressure (Indoor-Highest, Silent / Outdoor) (dB (A))	Indoor-Highest 39, Silent 26 / Outdoor-53	Indoor-Highest 40, Silent 26 / Outdoor-53	Indoor-Highest 45, Silent 26 / Outdoor-58	Indoor-Highest 50, Silent 26 / Outdoor-61
IDU Dimensions (Inch)	32 7/8 x 11 x 8 11/16	32 7/8 x 11 x 8 11/16	43 5/16 x 12 13/16 x 9 5/8	50 3/8 x 14 3/16 x 10 1/4
ODU Dimensions (Inch)	31 7/8 x 23 x 11	31 7/8 x 23 x 11	33 7/8 x 25 9/16 x 12 3/16	35 3/8 x 13 1/2 x 29 1/2
Std Operating Range (Cooling / Heating)	5°F-115°F / -22°F-75°F	5°F-115°F / -22°F-75°F	5°F-115°F / -22°F-75°F	5°F-115°F / -22°F-75°F
Long Pipe Connection (ft)	65ft for length, 16-32ft for height	65ft for length, 16-32ft for height	65ft for length, 16-32ft for height	65ft for length, 16-32ft for height

Standard Features

- SEER2 UP TO 25, EER2 14.5, ENERGY STAR.
- Low temp heating: -22°F (-30°C)* Low temp cooling: 5°F (-15°C).
- Integrated Wi-Fi plus the ConnectLife smart app with Alexa and Google Assistant control put easy operation right at your fingertips.
- Condenser base pan heater.
- Universal indoor units with Hi-Multi.
- Long connection pipes: 65ft length, up to 33 ft height.
- Vertical and Horizontal Auto Swing louver.
- Indoor Auto Cleaning mode with FrostClean™ technology.

*Suggested operating range. Unit will continue operation below stated temperatures.

Optional Features

- Wired control.
- Healthy Filter (Catechin, VC, HEPA, Jasmine aroma filter).

Hisense Canada Co., Ltd
Add: 2550 Meadowvale Boulevard, Unit 1, Mississauga,
ON, Canada L5N 8C2
Web site: www.hisense-canada.com

